

GV-Hub V2



The GV-Hub V2 adds four RS-232/RS-485 serial ports through your computer's USB port. The USB solution for serial port extension is perfect for any RS-485 to RS-232 conversion requirements, such as POS and PTZ applications.

Specifications		
OS Supported	32-bit	Windows XP / Windows Vista / Windows 7 / Windows Server 2008
	64-bit	Windows 7 / Windows Server 2008
Serial Interface	RS-232	Signal: DCD, RxD, TxD, DTR, GND, DSR, RTS, CTS
		Connector: DB9 Male x 4 (A, B, C, D)
	RS-485	Signal: D+, D-
		Connector: Terminal Block x 4(0 ~ 7, ∞ ~ 17.14 Ω)
	Serial Line Protection	16 KV ESD for All Signals
USB	Compliance	USB 2.0 Backward Compatible
	Speed	Full Speed 12 Mbps
Communication	Parity	None, Even, Odd
	Data Bit	7, 8
	Stop Bit	1, 2
	Flow Control	RTS / CTS, XON / XOFF
	Speed	600 bps to 115,200 bps
Environmental Conditions	Operation temperature	0~55°C / 32~131°F
	Humidity	5%~95% (non-condensing)
Dimensions(W x H x D)	103 x 30 x 125 (mm) / 4.06 x 1.18 x 4.92 (in)	
Installation Guide	GV-Hub V2	

Note:

1. All specifications are subject to change without notice.
2. When GV-Hub V2 works with [GV-Wiegand Capture](#), GV-Hub V2 does not support 64-bit Windows versions currently.